



**RANGE:** ONYX

**PRODUCT TYPE:** PORCELAIN

**INTENDED USE:** FOR INTERNAL WALL & FLOOR

| <u>Code</u>     | <u>Description</u> | <u>Size</u> | <u>Pcs/Box</u> | <u>M2/Box</u> | <u>M2/Pallet</u> | <u>Thickness</u> | <u>Faces</u> |
|-----------------|--------------------|-------------|----------------|---------------|------------------|------------------|--------------|
| QC-ONYXBL60120  | Onyx Black Opal    | 60x120      | 2              | 1.44          | 46.08            | 8                | 4            |
| QC-ONYXVER60120 | Onyx Verdigris     | 60X120      | 2              | 1.44          | 46.08            | 8                | 4            |

**ESSENTIAL CHARACTERISTICS**

**PERFORMANCE**

|                                             |                |
|---------------------------------------------|----------------|
| Slip Resistance                             | R9             |
| Resistance To Thermal Shock                 | Resistant      |
| Water Absorption                            | MIN E<0.10%    |
| Resistance To High/Low Acids And Alkalis    | Resistant      |
| Resistance to household chemicals           | A              |
| Modulus of Rupture (N/mm2)                  | > 15N/ mm2     |
| Min Resistance To Staining For Glazed Tiles | Class 4 / Pass |
| Breakage Strength                           | Min 1300 N     |
| Scratch Resistance                          | Resistant      |
| Stain Resistance                            | Resistant      |
| Abrasion Resistance                         | Resistant      |
| Crazing Resistance for Glazed Tiles         | Resistant      |