



TECHNICAL DATA SHEET

RANGE: LETAVOLE

PRODUCT TYPE: NON-RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Kg/box</u>	<u>Faces</u>
10004793	Letavole Beige	20x120	4	0.96	30.72	10	23	22
10004794	Letavole Grigio	20x120	4	0.96	30.72	10	23	22
10004795	Letavole Noce	20x120	4	0.96	30.72	10	23	22
10004796	Letavole Wenge	20x120	4	0.96	30.72	10	23	22

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R10
Water Absorption	E<0.5%
Breakage Strength	> 1300 N
Modulus of Rupture (N/mm2)	>35 N/ mm2
Impact Resistance	Resistant
Surface Deep Abrasion Resistance	Class 3
Linear Thermal Expansion Coefficient	Affirmative
Resistance to Thermal Shock	Resistant
Frost Resistance	Resistant
Resistance To High/Low Acids And Alkalis	Affirmative
Resistance To Household Chemicals	A
Stain Resistance	Class 5
Cementitious Adhesive type C2	>1.0 N/mm2