



RANGE: ANTIQUA

PRODUCT TYPE: PORCELAIN

INTENDED USE: FOR INTERNAL WALL AND FLOOR

| Code | Description | Size | Pcs/Box | M2/Box | M2/Pallet | Thickness | Faces |
|-----------|--------------------|--------|---------|--------|-----------|-----------|-------|
| GS-D8325 | Antiqua Anthracite | 60x60 | 5 | 1.8 | 57.6 | 8 | 22 |
| GMB-R1227 | Antiqua Anthracite | 60x120 | 3 | 2.16 | 60.48 | 8 | 11 |
| GS-D8324 | Antiqua Beige | 60x60 | 5 | 1.8 | 57.6 | 8 | 22 |
| GMB-R1223 | Antiqua Beige | 60x120 | 3 | 2.16 | 60.48 | 8 | 11 |
| GS-D8323 | Antiqua Off White | 60x60 | 5 | 1.8 | 57.6 | 8 | 22 |
| GMB-R1226 | Antiqua Off White | 60x120 | 3 | 2.16 | 60.48 | 8 | 11 |

ESSENTIAL CHARACTERISTICS

PERFORMANCE

| | |
|---|------------------------|
| Slip Resistance | R9 |
| Resistance To Thermal Shock | Resistant |
| Water Absorption | E<0.5% |
| Resistance To High/Low Acids And Alkalis | Resistant |
| Resistance to household chemicals | Resistant - Class A |
| Modulus of Rupture (N/mm ²) | >40N/ mm ² |
| Min Resistance To Staining For Glazed Tiles | Resistant |
| Breakage Strength | Min >1300 N |
| Crazing Resistance For Glazed Tiles | Resistant |
| Scratch Resistance | Resistant |
| Reaction To Fire | Resistant - Class A/A1 |
| Abrasion Resistance | Class 2 |