



TECHNICAL DATA SHEET

RANGE: SALT & PEPPER

PRODUCT TYPE: RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

Code	Description	Size	Pcs/Box	M2/Box	M2/Pallet	Thickness	Kg/box	Faces
TAA34208.BQ	Salt & Pepper Black	30x30	14	1.27	60.96	8	21	1
TAA34597.BQ	Salt & Pepper Grey	30x30	14	1.27	60.96	8	21	1
TAA34596.BQ	Salt & Pepper Light Beige	30x30	14	1.27	60.96	8	21	1

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R10
Water Absorption	E<0.5%
Breakage Strength	> 1500N
Modulus of Rupture (N/mm2)	>35 N/ mm2
Surface Deep Abrasion Resistance	175mm3
Linear Thermal Expansion Coefficient	MAX. 0.000008 / K
Resistance To Thermal Shock	Resistant
Crazing Resistance	Resistant
Freeze-thaw Resistance	Resistant
Moisture Expansion	0.2 mm/m
Impact Resistance	Min 0.6
Reaction to Fire	A1
Resistance To High/Low Acids And Alkalis	B
Resistance To Household Chemicals	B