



TECHNICAL DATA SHEET

RANGE: WHITE CARRARA

PRODUCT TYPE: RECTIFIED CERAMIC

INTENDED USE: FOR INTERNAL WALL

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Kg/box</u>	<u>Faces</u>
5203-L	White Carrara Gloss	30x60	5	0.9	54	8.5	14	6
5203-HL-7	White Carrara Gloss Décor	30x60	5	0.9	54	8.5	14	6
6385-L	White Carrara Matt	30x60	5	0.9	54	8.5	14	6
5203-HL-3	White Carrara Matt Décor	30x60	5	0.9	54	8.5	14	6

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	N/A
Water Absorption	18%
Breakage Strength	> 700 N
Moisture Expansion	0.01% Max
Modulus of Rupture (N/mm2)	>17 N/ mm2
Surface Deep Abrasion Resistance	Min 2
Resistance to Thermal Shock	10 Cycles Passed
Linear Thermal Expansion Coefficient	6 x 10
Crazing Resistance	04 Cycles Passed
Resistance To Household Chemicals	Class AA