



**RANGE:** TENBY

**PRODUCT TYPE:** PORCELAIN

**INTENDED USE:** FOR INTERNAL & EXTERNAL WALL AND FLOOR

Code	Description	Size	Pcs/Box	M2/Box	M2/Pallet	Thickness	Faces
CA5FTENBDDFA	Tenby Grey	59.5x59.5	4	1.4161	50.9796	10	24
CAN5TENBDDFA	Tenby Grey	59.5x120	2	1.428	57.12	10	13
CAR3TENBDDFA	Tenby Grey	120x120	1	1.44	51.84	10	7
CA5FTENBCDFA	Tenby White	59.5x59.5	4	1.4161	50.9796	10	24
CAN5TENBCDFA	Tenby White	59.5x120	2	1.428	57.12	10	13
CAR3TENBCDFA	Tenby White	120x120	1	1.44	51.84	10	7

#### **ESSENTIAL CHARACTERISTICS**

#### **PERFORMANCE**

Slip Resistance	R-11
Resistance To Thermal Shock	Resistant
Water Absorption	E<0.5%
Resistance To High/Low Acids And Alkalis	NPD
Resistance to household chemicals	A
Modulus of Rupture (N/mm2)	>35 N/ mm2
Min Resistance To Staining For Glazed Tiles	Pass
Breakage Strength	>1300 N
Crazing Resistance For Glazed Tiles	Affirmative
Thermal Shock Resistance	Pass
Ramp Slip Resistance	R-11
Reaction To Fire	A1
Outdoor Use	Only to be fitted on a flat concrete base/slab