



TECHNICAL DATA SHEET

RANGE: BETONICO

PRODUCT TYPE: RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

Code	Description	Size	Pcs/Box	M2/Box	M2/Pallet	Thickness	Faces
CBET.DAKSR792.RA01	Betonico Black	30x60	7	1.26	50.4	9	1
CBET.DAKSR794.RA01	Betonico Dark Beige	30x60	7	1.26	50.4	9	1
CBET.DAKSR791.RA01	Betonico Grey	30x60	7	1.26	50.4	9	1
CBET.DAKSR790.RA01	Betonico White-Grey	30x60	7	1.26	50.4	9	1

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R10
Water Absorption	E<0.4%
Breakage Strength	> 1500N
Modulus of Rupture (N/mm ²)	>40 N/ mm ²
Surface Deep Abrasion Resistance	PEI 4
Linear Thermal Expansion Coefficient	MAX. 0.000008 / K
Resistance To Thermal Shock	Resistant
Crazing Resistance	Resistant
Freeze-thaw Resistance	Resistant
Moisture Expansion	0.2 mm/m
Impact Resistance	Min 0.6
Reaction to Fire	A1
Resistance To High/Low Acids And Alkalis	A (low) B (high)

Resistance To Household Chemicals	A
-----------------------------------	---