



TECHNICAL DATA SHEET

RANGE: GALENA CARYN

PRODUCT TYPE: RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Kg/box</u>	<u>Faces</u>
CARYN100100SAT	Caryn Cream	100x100	2	1.9801	47.5224	10.5	42.29	8
CARYN75150	Caryn Cream	75x150	1	1.114	44.56	10.5	26.38	9
CARW100100SAT	Caryn White	100x100	2	1.9801	47.5224	10.5	42.29	8
CARYW75150	Caryn White	75x150	1	1.114	44.56	10.5	26.38	9

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	N/A
Water Absorption	E<0.5%
Breakage Strength	> 1100 N
Modulus of Rupture (N/mm2)	>30 N/ mm2
Surface Deep Abrasion Resistance	Class 4
Frost Resistance	Complies
Resistance To Low Acids And Alkalis	Min Class LB
Resistance To Household Chemicals	Min Class B
Stain Resistance	Min Class 3