



TECHNICAL DATA SHEET

RANGE: ONYX BLACK OPAL & VERDIGRIS

PRODUCT TYPE: RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Kg/box</u>	<u>Faces</u>
QC-ONYXBL60120	Onyx Black Opal	60x120	2	1.44	46.08	8	27.5	4
QC-ONYXVER60120	Onyx Verdigris	60x120	2	1.44	46.08	8	27.5	4

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	N/A
Water Absorption	E<0.08%
Breakage Strength	> 1500 N
Modulus of Rupture (N/mm2)	>37 N/ mm2
Linear Thermal Expansion Coefficient	6x10
Resistance to Thermal Shock	Min 10
Moisture Expansion	0.02 MAX
Crazing Resistance	Min 04
Resistance To High/Low Acids And Alkalis	Low - Class GLB, High - Class GHB
Resistance To Household Chemicals	AA
Stain Resistance	Class 3