



TECHNICAL DATA SHEET

RANGE: PARQUET

PRODUCT TYPE: NON-RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Kg/box</u>	<u>Faces</u>
GS-D8615	Parquet Cream	60x60	5	1.8	57.6	8	29.75	4
GS-D8616	Parquet Gris	60x60	5	1.8	57.6	8	29.75	4
GS-D8617	Parquet Oak	60x60	5	1.8	57.6	8	29.75	4
GS-D8613	Parquet White	60x60	5	1.8	57.6	8	29.75	4

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R10 (PTV+36)
Water Absorption	E<0.5%
Breakage Strength	> 1300 N
Modulus of Rupture (N/mm2)	>35 N/ mm2
Impact Resistance	Resistant
Resistance for Surface Abrasion for Glazed Tile	Class 4
Linear Thermal Expansion Coefficient	Resistant
Resistance to Thermal Shock	Resistant
Crazing Resistance	Resistant
Resistance To High/Low Acids And Alkalis	Resistant
Resistance To Household Chemicals	A
Stain Resistance	Class 5
Cementitious Adhesive type C2	>1.0 N/mm2