



TECHNICAL DATA SHEET

RANGE: BODO

PRODUCT TYPE: NON-RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

Code	Description	Size	Pcs/Box	M2/Box	M2/Pallet	Thickness	Kg/box	Faces
GS-D7646	Bodo Beige	30x60	8	1.44	57.6	8.5	26.9	20
GS-D7645	Bodo Grey	30x60	8	1.44	57.6	8.5	26.9	20
GS-D7644	Bodo White	30x60	8	1.44	57.6	8.5	26.9	20

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R10
Water Absorption	E<0.5%
Breakage Strength	> 1300 N
Modulus of Rupture (N/mm2)	>35 N/ mm2
Impact Resistance	Resistant
Surface Deep Abrasion Resistance	Class 3
Linear Thermal Expansion Coefficient	Affirmative
Resistance to Thermal Shock	Resistant
Crazing Resistance	Resistant
Frost Resistance	Resistant
Resistance To High/Low Acids And Alkalis	Affirmative
Resistance To Household Chemicals	A
Stain Resistance	Class 5
Cementitious Adhesive type C2	>1.0 N/mm2