



RANGE: BODO 100X100

PRODUCT TYPE: GLAZED PORCELAIN

INTENDED USE: FOR INTERNAL & EXTERNAL WALL AND FLOOR

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Faces</u>
BODBEI1MX1MR	Bodo Beige	100x100	2	1.98	47.52	10	7
BODGRY1MX1MR	Bodo Grey	100x100	2	1.98	47.52	10	7
BODWHT1MX1MR	Bodo White	100x100	2	1.98	47.52	10	7

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R-11
Resistance To Thermal Shock	Resistant
Water Absorption	E<0.5%
Resistance To High/Low Acids And Alkalis	NPD
Resistance to household chemicals	A
Modulus of Rupture (N/mm2)	>35 N/ mm2
Min Resistance To Staining For Glazed Tiles	Pass
Breakage Strength	>1300 N
Crazing Resistance For Glazed Tiles	Affirmative
Thermal Shock Resistance	Pass
Ramp Slip Resistance	R-11
Reaction To Fire	A1
Outdoor Use	Only to be fitted on a flat concrete base/slab