



TECHNICAL DATA SHEET

RANGE: MAUNAS

PRODUCT TYPE: RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Kg/box</u>	<u>Faces</u>
MMB-U603	Maunas White Matt	60x60	5	1.8	57.6	8	31.7	18
GMB-R1200	Maunas White Matt	60x120	3	2.16	60.48	8	39.5	9

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R9
Water Absorption	E<0.5%
Breakage Strength	> 1300 N
Modulus of Rupture (N/mm2)	>40 N/ mm2
Impact Resistance	Affirmative
Surface Deep Abrasion Resistance	Class 4
Linear Thermal Expansion Coefficient	Affirmative
Resistance to Thermal Shock	Affirmative
Frost Resistance	Resistant
Resistance To High/Low Acids And Alkalis	Affirmative
Resistance To Household Chemicals	A
Stain Resistance	Affirmative
Cementitious Adhesive type C2	>1.0 N/mm2