



**TECHNICAL DATA SHEET**

**RANGE:** BODO

**PRODUCT TYPE:** NON-RECTIFIED PORCELAIN

**INTENDED USE:** FOR INTERNAL WALL & FLOOR

Code	Description	Size	Pcs/Box	M2/Box	M2/Pallet	Thickness	Faces
GS-D7649	Bodo Beige	60x60	5	1.8	57.6	8	10
GS-D7648	Bodo Grey	60x60	5	1.8	57.6	8	10
GS-D7647	Bodo White	60x60	5	1.8	57.6	8	10

**ESSENTIAL CHARACTERISTICS**

**PERFORMANCE**

Slip Resistance	R10
Water Absorption	E<0.5%
Breakage Strength	> 1300 N
Modulus of Rupture (N/mm <sup>2</sup> )	>35 N/ mm <sup>2</sup>
Impact Resistance	Resistant
Surface Deep Abrasion Resistance	Class 3
Linear Thermal Expansion Coefficient	Affirmative
Resistance to Thermal Shock	Resistant
Crazing Resistance	Resistant
Frost Resistance	Resistant
Resistance To High/Low Acids And Alkalis	Affirmative
Resistance To Household Chemicals	A
Stain Resistance	Class 5
Cementitious Adhesive type C2	>1.0 N/mm <sup>2</sup>