



TECHNICAL DATA SHEET

RANGE: ANTIQUA

PRODUCT TYPE: NON-RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

Code	Description	Size	Pcs/Box	M2/Box	M2/Pallet	Thickness	Faces
GS-D7039	Antiqua Anthracite	30x60	8	1.44	57.6	8	45
GS-D8325	Antiqua Anthracite	60x60	5	1.8	57.6	8	22
GS-D7034	Antiqua Beige	30x60	8	1.44	57.6	8	45
GS-D8324	Antiqua Beige	60x60	5	1.8	57.6	8	22
GS-D7011	Antiqua Off White	30x60	8	1.44	57.6	8	45
GS-D8323	Antiqua Off White	60x60	5	1.8	57.6	8	22

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R9
Resistance To Thermal Shock	Resistant
Water Absorption	E<0.5%
Resistance To High/Low Acids And Alkalis	Resistant
Resistance to household chemicals	A
Modulus of Rupture (N/mm ²)	> 35N/ mm ²
Min Resistance To Staining For Glazed Tiles	Pass
Breakage Strength	>1300 N
Crazing Resistance For Glazed Tiles	Resistant
Cementitious Adhesive, Type C2	>1.0N/mm ²
Reaction to Fire	A1