



RANGE: RELIEF GLOSS WHITE

PRODUCT TYPE: CERAMIC

INTENDED USE: FOR INTERNAL WALLS

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Faces</u>
4405	Relief Gloss White	20x25	20	1	92	7	1
5445	Relief Gloss White	25x33	18	1.5	76.5	7	1
9405	Relief Gloss White	25x40	14	1.4	75.6	7	1

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	N/A
Resistance To Thermal Shock	Resistant
Water Absorption	E<10.0%
Resistance To High/Low Acids And Alkalis	NPD
Resistance to household chemicals	A
Modulus of Rupture (N/mm2)	>24 N/ mm2
Min Resistance To Staining For Glazed Tiles	Pass/ Class-5
Breakage Strength	>600 N
Crazing Resistance For Glazed Tiles	Affirmative
Thermal Shock Resistance	Pass
Cementitious Adhesive	>0.5 N/mm2
Reaction To Fire	A1
Moisture Expansion (mm/m)	0.01976