



TECHNICAL DATA SHEET

RANGE: OCEANO

PRODUCT TYPE: RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Kg/Box</u>	<u>Faces</u>
OCEPOL6060	Oceano Polished	60x60	4	1.44	57.6	9	28	5
OCEPOL60X120	Oceano Polished	60x120	2	1.44	48.96	9	30	4

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	N/A
Water Absorption	E<0.05%
Breakage Strength	> 2000 N
Modulus of Rupture (N/mm2)	>40 N/ mm2
Impact Resistance	Min 0.55
Surface Deep Abrasion Resistance	Min Class-3
Frost Resistance	Resistant
Resistance to Thermal Shock	Resistant
Linear Thermal Expansion Coefficient	Max 6.5 x 10
Crazing Resistance	Min 10 Cycle
Resistance To Household Chemicals	Resistant
Stain Resistance	Resistant
Fire Resistance	Fireproof