



RANGE: BODO

PRODUCT TYPE: PORCELAIN

INTENDED USE: FOR INTERNAL WALL AND FLOOR

Code	Description	Size	Pcs/Box	M2/Box	M2/Pallet	Thickness	Faces
GS-D7649	Bodo Beige	60x60	5	1.8	57.6	8	10
GMB-R1281	Bodo Beige	60x120	3	2.16	60.48	8	5
GS-D7648	Bodo Grey	60x60	5	1.8	57.6	8	10
GMB-R1280	Bodo Grey	60x120	3	2.16	60.48	8	5
GS-D7647	Bodo White	60x60	5	1.8	57.6	8	10
GMB-R1282	Bodo White	60x120	3	2.16	60.48	8	5

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R10 (PTV36+)
Resistance To Thermal Shock	Resistant
Water Absorption	E<0.5%
Resistance To High/Low Acids And Alkalis	Resistant
Resistance to household chemicals	Resistant - Class A
Modulus of Rupture (N/mm ²)	>40N/ mm ²
Min Resistance To Staining For Glazed Tiles	Resistant
Breakage Strength	Min >1300 N
Crazing Resistance For Glazed Tiles	Resistant
Scratch Resistance	Resistant
Reaction To Fire	Resistant - Class A/A1
Abrasion Resistance	Class 2