



**RANGE:** AMANI

**PRODUCT TYPE:** PORCELAIN

**INTENDED USE:** FOR INTERNAL WALL & FLOOR

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Faces</u>
GS-D8978	Amani Cream	60x60	5	1.8	57.6	8	9
GS-D8980	Amani Grey	60x60	5	1.8	57.6	8	9
GS-D8999	Amani White	60x60	5	1.8	57.6	8	9

<u>ESSENTIAL CHARACTERISTICS</u>	<u>PERFORMANCE</u>
Slip Resistance	R9
Resistance To Thermal Shock	Affirmative
Water Absorption	E<0.5%
Resistance To High/Low Acids And Alkalis	Affirmative
Resistance to household chemicals	A
Resistance to Surface Abrasion for Glazed Tile	Class -
Modulus of Rupture (N/mm <sup>2</sup> )	>40N/ mm <sup>2</sup>
Breakage Strength	MIN 1300 N
Stain Resistance	Affirmative
Abrasion Resistance	PEI 3
Frost Resistance	Resistant
Reaction to Fire	A1