



TECHNICAL DATA SHEET

RANGE: ONI POLISHED

PRODUCT TYPE: RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Kg/box</u>	<u>Faces</u>
ONIPOLB60120	Oni Blue	60x120	2	1.44	46.08	9	34.5	16
ONIPOLC60120	Oni Coral	60x120	2	1.44	46.08	9	34.5	16
ONIPOLP60120	Oni Pearl	60x120	2	1.44	46.08	9	34.5	16
ONIWHI60120	Oni White	60x120	2	1.44	46.08	9	34.5	16

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	N/A
Water Absorption	E<0.5%
Breakage Strength	> 1300 N
Modulus of Rupture (N/mm2)	>35 N/ mm2
Resistance to Thermal Shock	Resistant
Crazing Resistance	Resistant
Resistance To High/Low Acids And Alkalis	A
Resistance To Household Chemicals	A
Stain Resistance	5