



RANGE: BODO 100X100

PRODUCT TYPE: GLAZED PORCELAIN

INTENDED USE: FOR INTERNAL & EXTERNAL WALL AND FLOOR

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Faces</u>
GMB-R1281	Bodo Beige	60x120	3	2.16	60.48	8	5
GMB-R1280	Bodo Grey	60x120	3	2.16	60.48	8	5
GMB-R1282	Bodo White	60x120	3	2.16	60.48	8	5

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R10 (PTV36+)
Resistance To Thermal Shock	Resistant
Water Absorption	E<0.5%
Resistance To High/Low Acids And Alkalis	Resistant
Resistance to household chemicals	Resistant - Class A
Modulus of Rupture (N/mm2)	>40N/ mm2
Min Resistance To Staining For Glazed Tiles	Resistant
Breakage Strength	Min >1300 N
Crazing Resistance For Glazed Tiles	Resistant
Scratch Resistance	Resistant
Reaction To Fire	Resistant - Class A/A1
Abrasion Resistance	Class 2 (Beige & White Class 3)
Outdoor Use	Only to be fitted on a flat concrete base/slab