



**RANGE:** UDDO GOLD

**PRODUCT TYPE:** PORCELAIN

**INTENDED USE:** FOR INTERNAL & EXTERNAL WALLS

| <u>Code</u> | <u>Description</u> | <u>Size</u> | <u>Pcs/Box</u> | <u>M2/Box</u> | <u>M2/Pallet</u> | <u>Thickness</u> | <u>Faces</u> |
|-------------|--------------------|-------------|----------------|---------------|------------------|------------------|--------------|
| GS-N9025    | Uddo Gold          | 20x120      | 5              | 1.2           | 38.4             | 8.5              | 17           |

**ESSENTIAL CHARACTERISTICS**

**PERFORMANCE**

|                                                 |                      |
|-------------------------------------------------|----------------------|
| Slip Resistance                                 | R-9                  |
| Reaction To Fire                                | A1 <sub>FL</sub> /A1 |
| Water Absorption                                | E<0.5%               |
| Release of Dangerous Substance                  | NPD                  |
| Min Resistance To Staining For Glazed Tiles     | Pass                 |
| Breakage Strength                               | >1300 N              |
| Ramp Slip Resistance                            | R-9 CLASS-A          |
| Resistance to Surface Abrasion for Glazed Tiles | CLASS-4              |
| Bond Strength/Adhesion                          | >1N/MM <sub>2</sub>  |
| Thermal Shock Resistance                        | Pass                 |
| Use in Areas with Heavy Foot Traffic            | Pass                 |