## Ceramica Impex

**RANGE:** URBAN

**PRODUCT TYPE:** CERAMIC

**INTENDED USE:** FOR INTERNAL WALL

| <u>Code</u>                                 | <u>Description</u>    | <u>Size</u> | Pcs/Box     | M2/Box | M2/Pallet | <b>Thickness</b> | <u>Faces</u> |  |
|---|-----------------------|-------------|-------------|--------|-----------|------------------|--------------|--|
| MAS-5130R                                   | Urban Grey            | 40x80       | 4           | 1.28   | 61.44     | 10               | 1            |  |
| MAS-5131RT                                  | Urban Light Grey      | 40x80       | 4           | 1.28   | 71.68     | 10               | 1            |  |
| RM-5132R                                    | Urban Patchwork Décor | 40x80       | 4           | 1.28   | 61.44     | 10               | 1            |  |
| ESSENTIAL CHARACTERISTICS                   |                       | PERFORMA    | PERFORMANCE |        |           |                  |              |  |
| Slip Resistance                             |                       | N/A         | N/A         |        |           |                  |              |  |
| Resistance To Thermal Shock                 |                       | Resistant   | Resistant   |        |           |                  |              |  |
| Water Absorption                            |                       | E<10%       | E<10%       |        |           |                  |              |  |
| Resistance To High/Low Acids And Alkalis    |                       | NPD         | NPD         |        |           |                  |              |  |
| Resistance to household chemicals           |                       | А           | A           |        |           |                  |              |  |
| Modulus of Rupture (N/mm2)                  |                       | >20N/ mm    | >20N/ mm2   |        |           |                  |              |  |
| Min Resistance To Staining For Glazed Tiles |                       | Pass        | Pass        |        |           |                  |              |  |
| Breakage Strength                           |                       | >600N       | >600N       |        |           |                  |              |  |
| Crazing Resistance For Glazed Tiles         |                       | Affirmative | Affirmative |        |           |                  |              |  |
| Cementitious Adhesive, Type C1              |                       | >0.5N/mm    | >0.5N/mm2   |        |           |                  |              |  |
| Reaction to Fire                            |                       | A1          | A1          |        |           |                  |              |  |