



## **TECHNICAL DATA SHEET**

**RANGE:** OREA

**PRODUCT TYPE:** RECTIFIED CERAMIC

**INTENDED USE:** FOR INTERNAL WALL

| <u>Code</u> | <u>Description</u>   | <u>Size</u> | <u>Pcs/Box</u> | <u>M2/Box</u> | <u>M2/Pallet</u> | <u>Thickness</u> | <u>Kg/Box</u> | <u>Faces</u> |
|-------------|----------------------|-------------|----------------|---------------|------------------|------------------|---------------|--------------|
| D412D944Q1  | Orea Bone Matt       | 39.5x79.5   | 5              | 1.57          | 75.36            | 8                | 21            | 10           |
| D412D944R1  | Orea Light Grey Matt | 39.5x79.5   | 5              | 1.57          | 75.36            | 8                | 21            | 10           |

### **ESSENTIAL CHARACTERISTICS**

### **PERFORMANCE**

|                                   |            |
|-----------------------------------|------------|
| Slip Resistance                   | N/A        |
| Water Absorption                  | E<9%       |
| Breaking Strength                 | 700N       |
| Modulus of Rupture (N/mm2)        | >15 N/ mm2 |
| Resistance to Thermal Shock       | Pass       |
| Stain Resistance                  | Class 5    |
| Resistance To Household Chemicals | Class A    |