



## **TECHNICAL DATA SHEET**

**RANGE:** NORDIC

**PRODUCT TYPE:** NON-RECTIFIED PORCELAIN

**INTENDED USE:** FOR INTERNAL WALL & FLOOR

| <u>Code</u> | <u>Description</u> | <u>Size</u> | <u>Pcs/Box</u> | <u>M2/Box</u> | <u>M2/Pallet</u> | <u>Thickness</u> | <u>Kg/box</u> | <u>Faces</u> |
|-------------|--------------------|-------------|----------------|---------------|------------------|------------------|---------------|--------------|
| GS-D3652    | Nordic Dark        | 15x60       | 16             | 1.44          | 57.6             | 9                | 24.82         | 10           |
| GS-D3649    | Nordic Light       | 15x60       | 16             | 1.44          | 57.6             | 9                | 24.82         | 10           |
| GS-D3654    | Nordic Soft Pearl  | 15x60       | 14             | 1.26          | 63               | 9                | 24.82         | 10           |

### **ESSENTIAL CHARACTERISTICS**

### **PERFORMANCE**

|                                          |             |
|------------------------------------------|-------------|
| Slip Resistance                          | R9          |
| Water Absorption                         | E<0.5%      |
| Breakage Strength                        | > 1300 N    |
| Modulus of Rupture (N/mm2)               | >35 N/ mm2  |
| Impact Resistance                        | Resistant   |
| Surface Deep Abrasion Resistance         | Class 3     |
| Linear Thermal Expansion Coefficient     | Affirmative |
| Resistance to Thermal Shock              | Resistant   |
| Crazing Resistance                       | Resistant   |
| Frost Resistance                         | Resistant   |
| Resistance To High/Low Acids And Alkalis | Affirmative |
| Resistance To Household Chemicals        | A           |
| Stain Resistance                         | Class 5     |
| Cementitious Adhesive type C2            | >1.0 N/mm2  |