



TECHNICAL DATA SHEET

RANGE: BETONICO

PRODUCT TYPE: RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

Code	Description	Size	Pcs/Box	M2/Box	M2/Pallet	Thickness	Kg/box	Faces
CBET.DAK62792.RA01	Betonico Black	60x60	4	1.44	46.08	9	29.1	1
CBET.DAK62794.RA01	Betonico Dark Beige	60x60	4	1.44	46.08	9	29.1	1
CBET.DAK62791.RA01	Betonico Grey	60x60	4	1.44	46.08	9	29.1	1
CBET.DAK62790.RA01	Betonico White-Grey	60x60	4	1.44	46.08	9	29.1	1

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R10
Water Absorption	E<0.4%
Breakage Strength	> 1500N
Modulus of Rupture (N/mm2)	>40 N/ mm2
Surface Deep Abrasion Resistance	PEI 4
Linear Thermal Expansion Coefficient	MAX. 0.000008 / K
Resistance To Thermal Shock	Resistant
Crazing Resistance	Resistant
Freeze-thaw Resistance	Resistant
Moisture Expansion	0.2 mm/m
Impact Resistance	Min 0.6
Reaction to Fire	A1
Resistance To High/Low Acids And Alkalis	A (low) B (high)
Resistance To Household Chemicals	A