



TECHNICAL DATA SHEET

RANGE: SALT & PEPPER

PRODUCT TYPE: RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Kg/box</u>	<u>Faces</u>
TAK63061	Salt & Pepper Beige	60x60	3	1.08	34.56	9	23.7	1
TAK62069	Salt & Pepper Black	60x60	4	1.44	46.08	9	29.1	1
TAK62076	Salt & Pepper Light Grey	60x60	4	1.44	46.08	9	29.1	1
TAK63060	Salt & Pepper White	60x60	3	1.08	34.56	9	23.7	1

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R10
Water Absorption	E<0.4%
Breakage Strength	> 1500N
Modulus of Rupture (N/mm2)	>40 N/ mm2
Surface Deep Abrasion Resistance	135mm3
Linear Thermal Expansion Coefficient	MAX. 0.000008 / K
Resistance To Thermal Shock	Resistant
Crazing Resistance	Resistant
Freeze-thaw Resistance	Resistant
Moisture Expansion	0.2 mm/m
Impact Resistance	Min 0.6
Reaction to Fire	A1
Resistance To High/Low Acids And Alkalis	A
Resistance To Household Chemicals	A