



TECHNICAL DATA SHEET

RANGE: ONYX MATT

PRODUCT TYPE: RECTIFIED PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

Code	Description	Size	Pcs/Box	M2/Box	M2/Pallet	Thickness	Kg/Box	Faces
KB.ONYXCM120	Onyx Cream	120x120	1	1.44	43.2	8	27.9	5
KB.ONYXGR120	Onyx Grey	120x120	1	1.44	43.2	8	27.9	5
KB.ONYXWH120	Onyx White	120x120	1	1.44	43.2	8	27.9	5

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R9
Water Absorption	E<0.5%
Breakage Strength	> 1300 N
Modulus of Rupture (N/mm2)	>45 N/ mm2
Impact Resistance	Affirmative
Surface Deep Abrasion Resistance	Class 3
Linear Thermal Expansion Coefficient	Affirmative
Resistance To Thermal Shock	Affirmative
Frost Resistance	Resistant
Resistance To High/Low Acids And Alkalis	Affirmative
Resistance To Household Chemicals	A
Stain Resistance	Affirmative
Reaction to Fire	A1
Cementitious Adhesive type C2	>1.0N/mm2