



RANGE: PATTERNED

PRODUCT TYPE: PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

Code	Description	Size	Pcs/Box	M2/Box	M2/Pallet	Thickness	Faces
GS-D4862	D M J Blue	33x33	13	1.42	65.32	8	1
GS-D4860	D M J Grey	33x33	13	1.42	65.32	8	1
GS-D4885	Geometric A R Black	33x33	13	1.42	65.32	8	1
GS-D4864	H D Black	33x33	13	1.42	65.32	8	1
GS-D4863	H D Grey	33x33	13	1.42	65.32	8	1
GS-D4865	W Y Grey	33x33	13	1.42	65.32	8	1

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R9
Resistance To Thermal Shock	Resistant
Water Absorption	E<0.5%
Resistance To High/Low Acids And Alkalis	NPD
Resistance to household chemicals	A
Modulus of Rupture (N/mm ²)	> 35N/ mm ²
Min Resistance To Staining For Glazed Tiles	Pass / Class-5
Breakage Strength	>1300 N
Crazing Resistance for Glazed Tiles	Resistant
Resistance to Surface Abrasion	Pass / Class-4
Cementitious Adhesive	>1.0 N/mm ²
Reaction to Fire	A1