



RANGE: ONYX POLISHED

PRODUCT TYPE: PORCELAIN

INTENDED USE: FOR INTERNAL WALL & FLOOR

| Code | Description | Size | Pcs/Box | M2/Box | M2/Pallet | Thickness | Faces |
|--------------|-------------|---------|---------|--------|-----------|-----------|-------|
| KB.ONYXCM120 | Onyx Cream | 120x120 | 1 | 1.44 | 43.2 | 8 | 5 |
| KB.ONYXGR120 | Onyx Grey | 120x120 | 1 | 1.44 | 43.2 | 8 | 5 |
| KB.ONYXWH120 | Onyx White | 120x120 | 1 | 1.44 | 43.2 | 8 | 5 |

ESSENTIAL CHARACTERISTICS

PERFORMANCE

| | |
|--|------------------------|
| Slip Resistance | N/A |
| Resistance To Thermal Shock | Affirmative |
| Water Absorption | E<0.5% |
| Resistance To High/Low Acids And Alkalis | Affirmative |
| Surface Deep Abrasion Resistance | Class 4 |
| Modulus of Rupture (N/mm ²) | >40 N/ mm ² |
| Breakage Strength | > 1300 N |
| Impact Resistance | Affirmative |
| Stain Resistance | Affirmative |
| Frost Resistance | Resistant |
| Reaction to Fire | A1 |