



**RANGE:** FOG

**PRODUCT TYPE:** PORCELAIN

**INTENDED USE:** FOR INTERNAL WALL & FLOOR

| <u>Code</u>  | <u>Description</u> | <u>Size</u> | <u>Pcs/Box</u> | <u>M2/Box</u> | <u>M2/Pallet</u> | <u>Thickness</u> | <u>Faces</u> |
|--------------|--------------------|-------------|----------------|---------------|------------------|------------------|--------------|
| FOGANPOL6060 | Fog Anthracite     | 60x60       | 4              | 1.44          | 57.6             | 9                | 7            |
| FOGGYPOL6060 | Fog Light Grey     | 60x60       | 4              | 1.44          | 57.6             | 9                | 7            |

**ESSENTIAL CHARACTERISTICS**

**PERFORMANCE**

|                                             |           |
|---------------------------------------------|-----------|
| Slip Resistance                             | N/A       |
| Resistance To Thermal Shock                 | Resistant |
| Water Absorption                            | E<0.20%   |
| Resistance To High/Low Acids And Alkalis    | NPD       |
| Resistance to household chemicals           | A         |
| Modulus of Rupture (N/mm2)                  | >40 N/mm2 |
| Min Resistance To Staining For Glazed Tiles | Pass      |
| Breakage Strength                           | >1800 N   |
| Glossiness                                  | Min 90%   |
| MOH'S Hardness                              | Class 5   |
| Resistance to Surface Abrasion              | Class 3   |
| Reaction to Fire                            | A1        |