



TECHNICAL DATA SHEET

RANGE: 9405 _ 9505

PRODUCT TYPE: NON-RECTIFIED CERAMIC

INTENDED USE: FOR INTERNAL WALL

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>Pcs/Box</u>	<u>M2/Box</u>	<u>M2/Pallet</u>	<u>Thickness</u>	<u>Kg/box</u>	<u>Faces</u>
9405	Relief Super White	25x40	14	1.4	75.6	7	19.04	1
9505	Flat Gloss White	25x40	14	1.4	75.6	8	19.04	1

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	N/A
Water Absorption	E<20%
Breakage Strength	> 200 N
Modulus of Rupture (N/mm2)	>20 N/ mm2
Resistance to Surface Abrasion for Glazed Tile	Class - 4
Linear Thermal Expansion Coefficient	6X10 / °C
Resistance To Thermal Shock	Resistant
Moisture Expansion	(%) 0.01976
Crazing Resistance for Glazed Tiles	Affirmative
Resistance To High/Low Acids And Alkalis	Affirmative
Resistance To Household Chemicals	A
Resistance to Staining	Class-5
Reaction to Fire	A1
Cementitious Adhesive type C1	>0.5N/mm2