



RANGE: TENBY

PRODUCT TYPE: PORCELAIN

INTENDED USE: FOR INTERNAL & EXTERNAL WALL AND FLOOR

Code	Description	Size	Pcs/Box	M2/Box	M2/Pallet	Thickness	Faces
CA5FTENBHDF A	Tenby Anthracite	59.5x59.5	4	1.4161	50.9796	10	24
CAN5TENBHDF A	Tenby Anthracite	59.5x120	2	1.428	57.12	10	13
CAR3TENBHDF A	Tenby Anthracite	120x120	1	1.44	51.84	10	7
CA5FTENBBDF A	Tenby Beige	59.5x59.5	4	1.4161	50.9796	10	24
CAN5TENBBDF A	Tenby Beige	59.5x120	2	1.428	57.12	10	13
CAR3TENBBDF A	Tenby Beige	120x120	1	1.44	51.84	10	7

ESSENTIAL CHARACTERISTICS

PERFORMANCE

Slip Resistance	R-11
Resistance To Thermal Shock	Resistant
Water Absorption	E<0.5%
Resistance To High/Low Acids And Alkalis	NPD
Resistance to household chemicals	A
Modulus of Rupture (N/mm ²)	>35 N/ mm ²
Min Resistance To Staining For Glazed Tiles	Pass
Breakage Strength	>1300 N
Crazing Resistance For Glazed Tiles	Affirmative
Thermal Shock Resistance	Pass
Ramp Slip Resistance	R-11
Reaction To Fire	A1
Outdoor Use	Only to be fitted on a flat concrete base/slab