



## Range: Patterned 33x33

### Technical data

GS-D4885 PATTERNED GEOMETRIC A R BLACK 33X33

GS-D4863 PATTERNED H D GREY 33X33

GS-D4864 PATTERNED H D BLACK 33X33

GS-D4861 PATTERNED D M J BEIGE 33X33

GS-D4862 PATTERNED D M J BLUE 33X33

GS-D4860 PATTERNED D M J GREY 33X33

GS-D4865 PATTERNED W Y GREY 33X33

### Product type:

DRY PRESSED GLAZED PORCELAIN TILES

### Intended use(s):

FOR INTERNAL WALL AND FLOOR

Essential Characteristics	Performance
Resistance To Thermal Shock	Resistant
Water Absorption	E<0.5%
Resistance To High/Low Acids And Alkalis	NPD
Resistance to household chemicals	A
Modulus of Rupture (N/mm <sup>2</sup> )	>35 N/ mm <sup>2</sup>
Min Resistance To Staining For Glazed Tiles	Pass / Class-5
Resistance To Surface Abrasion	Pass / Class-4
Breakage Strength	>1300 N
Crazing Resistance For Glazed Tiles	Affirmative
Thermal Shock Resistance	Resistant
Cementitious Adhesive	>1.0 N/mm <sup>2</sup>
Slip Resistance	R-9
Reaction To Fire	A1
Durability For:	
-Internal Use On Walls	Pass
-Internal Use On Flooring	Pass